## **Technical data sheet**

Clamp clip 2056, U-foot, single, metal pressure trough, A2

### Item number: 1188404





Clamp clip with U-foot, metal pressure trough with rounded edges to protect the cable. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For slot width 18–22 mm. With 1-start screw thread on pressure trough, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for mounting indoors and outdoors. We recommend the use of a counter-trough.



#### Master data

1188404
BS-U1-M-16 A2
Clamp clip 2056
OBO
12-16mm
Stainless steel
Bright, treated
100
Piece
3.619 kg
kg/100 pc.


# **Technical data sheet**

Clamp clip 2056, U-foot, single, metal pressure trough, A2

### Item number: 1188404



Dimensions



	Length	22.5 mm
	Width	20 mm
	Height	44 mm
	Plate thickness	1.5 mm
	Dimension A	22.5 mm
	Dimension B	20 mm
	Dimension C	28 mm
	Dimension G (mm)	M6
	Dimension H	44 mm
	Dimension L	34 mm
	Dimension t	1.5 mm

**Technical data** 

Number of cables/pipes	1
For pipe diameter, max.	16 mm
For pipe diameter, min.	12 mm
for rail with slot width (with inter- val), max.	22 mm
for rail with slot width (with inter- val), min.	18 mm
Thread	M6
Halogen-free	yes
Length of external dimensions	28 mm
Max. Tightening torque	3 Nm
With metal trough	yes
Mounting type	Profile rail
Slot width	10 mm
Clamping range D, max.	16 mm
Clamping range D, min.	12 mm
Surface addition	Untreated
Material addition	Rustproof steel