# Technical data sheet

## Clamp clip 2056, U-foot, single, metal pressure trough, A2



**Item number: 1188407** 



Clamp clip with U-foot, metal pressure trough with rounded edges to protect the cable. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For slot width 18–22 mm. With 1-start screw thread on pressure trough, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for mounting indoors and outdoors. We recommend the use of a counter-trough.



A2

Stainless steel

2B

Bright, treated

#### Master data

Item number	1188407
Туре	BS-U1-M-22 A2
Description 1	Clamp clip 2056
Manufacturer	OBO
Dimension	16-22mm
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	100
Unit of quantity	Piece
Weight	4.285 kg
Weight unit	kg/100 pc.

### **Technical data sheet**

### Clamp clip 2056, U-foot, single, metal pressure trough, A2



**Item number: 1188407** 

SW 10/

PZ3

22,5

28

#### **Dimensions** 22.5 mm Length Width 27 mm 18 27 Height 51 mm Plate thickness 1.5 mm 1,5 11 Dimension A 22.5 mm Dimension B 27 mm Ø22 51 Dimension C 28 mm M6 Dimension G (mm) Dimension H 51 mm 34 M6 Dimension L 34 mm Dimension t 1.5 mm

#### **Technical data** Number of cables/pipes 22 mm For pipe diameter, max. For pipe diameter, min. 16 mm for rail with slot width (with inter-22 mm val), max. for rail with slot width (with inter-18 mm val), min. Thread M6 Halogen-free yes 28 mm Length of external dimensions Max. Tightening torque 3 Nm With metal trough yes Mounting type Profile rail Slot width 10 mm Clamping range D, max. 22 mm Clamping range D, min. 16 mm Surface addition Untreated

Rustproof steel

Material addition